



**BLACK LINE
SAE 10W-60**

API SL Package Performance

Wellrun BLACK LINE 10W-60, belongs to the latest generation of engine lubricants, specifically formulated to satisfy the demand when is required an outstanding product in terms of engine protection and performances, for powerful engines of any kind operating at any condition (Full synthetic cars, high output engines, extreme driving conditions as rallies, off road and desert temperature).

CHARACTERISTICS, typical

WELLRUN BLACK LINE		10W-60
Viscosity at 100°C	mm ² /s	24.5
Viscosity at -25°C	mPa	3350
Viscosity Index		207
Pour Point	°C	-45
Flash Point C.O.C.	°C	210
Mass. Density at 15°C	kg/l	0.868

PROPERTIES AND PERFORMANCES

The synthetic component strengthens the oil film which adheres tenaciously to metal surfaces even when the engine has been standing for some time, thus ensuring easy starting and greatly reducing wear under high load conditions.

The wide viscosity range 10W-60 assures the proper viscosity of the oil in every part of the engine, at any driving condition, at any ambient temperature.

The outstanding "stay-in-grade" quality, shown in the BOSCH Injector Shear Stability test, represents an important guarantee of viscosity stability, even after an extended period of extreme service.

The phosphorus level in the oil has been kept below 0.08% wt. In order to ensure maximum life of emission exhaust catalysts. This has been achieved without compromising the anti-wear and antioxidant qualities of the oil, as demonstrated in the severe TOYOTA test, NISSAN Turbo test, as well as the API and CCMC sequences tests.

The inclusion of a low-volatility, thermally-stable synthetic component minimizes oil consumption.

The special synthetic-fortified formulation ensures high performance in terms of detergent/dispersant, antirust, antifoam, anti-oxidation and anti-wear properties.

APPLICATIONS

Wellrun BLACK LINE, 10W-60 is an ultra high performance synthetic lubricant for use in all modern aspirated and turbocharged cars under the most severe and varied operating conditions, such as high temperature motorway driving or low temperature stop and go.

Please observe the manufacturer's specifications when selecting products!



SPECIFICATIONS

Wellrun BLACK LINE 10W-60 complies with the requirements of the following specifications:

- API SL Package Performance

AAVG, juni '04
GEPRINT: dinsdag 10 oktober 2006